



**PRODUCT NOTE:**

1. TESTED AND APPROVED FOR INSTALLATIONS UP TO 5000mm DEEP.
2. INTERNAL COATING OF ACID RESISTANT TAR EPOXY PAINT.
3. MPa RATING FOR GRC - 60MPa @ 28 DAYS.
4. LARGE RANGE OF CONCRETE SURROUNDS AND COVERS TO SUIT ALL LOAD RATINGS.
5. AVAILABLE EXTRAS:
  - STEP IRONS
  - 300mm RISERS
  - STAINLESS STEEL BASKET FITTED WITH Ø3mm HOLES FOR LINT TRAP
6. ALL PIPE FITTINGS ARE Ø100mm PVC
7. OTHER PVC PIPE SIZES AVAILABLE UPON REQUEST
8. INSTALLATION INSTRUCTIONS MUST BE FOLLOWED.
9. COVER WILL ADD TO OVERALL DEPTH

PRODUCT CODE	CAPACITY (L)	A	B	C	D	E	MASS (KG) PIT ONLY
VAMDCL 2	200	600	600	600	1125	325	115
VAMDCL 4	400	900	900	600	1075	275	205
VAMDCL 6	600	900	900	750	1075	125	230
VAMDCL 8	800	1200	1200	720	1225	305	375
VAMDCL 10	1000	1200	1200	900	1525	425	475
VAMDCL 12	1200	1200	1200	1075	1525	250	510
VAMDCL 15	1500	1200	1200	1350	1825	275	570

**SPECIFICATION**

Glass Reinforced Concrete Straining & Cooling Pit must be free of steel reinforcement to prevent corrosion.  
 Straining & Cooling Pit to be Mascot Engineering GRC ..... litre, model number VAMDCL ..... complete with Gastight Access Covers to suit Class ..... load rating to AS3996.  
 Products to be installed as per the manufacturers installation instructions.

© Copyright



PRODUCT DESCRIPTION:

VIC STRAINING & COOLING PIT

ph: 1300 885 295  
 fax: 1300 885 296  
 email: sales@mascoteng.com.au  
 www.mascotengineering.com.au

SCALE:

NTS

REVISION:

A

DRAWING No:

TW.VIC.CP.001